

0.50mm Pitch FFC/FPC HRS– F31S Series

VERTICAL ZIF FLEX CONNECTOR

HRS-F31S series is a 0.50mm pitch vertical ZIF flex connector with a vertical flip locking mechanism, surface mount termination, and dual contacts. It features a height of 5.80mm and comes in 10 to 70 contacts. This series features a cable thickness of 0.30mm and provides enhanced durability of 30 mating cycles. The connectors come with a robust design and prevent solder and flux wicking. These are ideal for automotive, data, industrial, communication, consumer, and medical applications

- Strong FFC/FPC retention makes it vibration-proof
- Dual contact points ensure enhanced contact stability
- Ensures high solderability and high durability
- Wide operating temperature range of -40°C to $+105^{\circ}\text{C}$
- USCAR-2 T3V2 qualified

FEATURES

- ZIF (Zero Insertion Force) mechanism
- Vertical flip locking mechanism
- Dual contact points
- Design against solder and flux wicking
- High-temperature thermoplastic housing
- 10 to 70 positions available
- Lead and halogen-free



TARGET MARKETS



BENEFITS

- Absence of frictional mating wear results in high mating cycle life
- Easy to operate and strong FFC/FPC retention makes it vibration-proof
- Ensures enhanced contact stability
- Ensures high solderability
- Wide operating temperature range of -40°C to $+105^{\circ}\text{C}$
- Comprehensive range to satisfy different customer requirements
- Meets environmental, health and safety requirements

TECHNICAL INFORMATION

MATERIAL

- Housing: LCP, Natural color (UL94V-0)
- Actuator: LCP, Black color (UL94V-0)
- Contact: Phosphor bronze, T=0.15mm
- Anchor-plate: Brass, T=0.40mm
- Mylar: T=0.10mm, Thermostable, Brown color

MECHANICAL PERFORMANCE

- FFC/FPC Retention Force: 20gf/pin
- Terminal Retention Force: 100gf/terminal min.
- Anchor-plate Retention Force: 500gf/plate min.
- Durability: 30 mating cycles

ELECTRICAL PERFORMANCE

- Voltage Rating: 50V AC/DC
- Current Rating: 0.5A
- Contact Resistance: 30MΩ max.
- Insulation Resistance: 500MΩ min.
- Dielectric Withstanding Voltage: No short or breakdown after 500V AC, 2mA, 1min.

PACKAGING

- Tape & Reel

APPROVALS AND CERTIFICATIONS

- UL File Number: E106764
- RoHS compliant

SPECIFICATION

- Product Specification: IS.EQC.034

ENVIRONMENTAL

- Operating Temperature Range: -40°C to +105°C

TARGET MARKETS/APPLICATIONS



Car Multimedia
Car Navigation
Dashboard
PND



Base Station
Power
Switches



Notebook
Tablets
Wearables
Gaming
DSC
LCD & PDP TV



Router
Server
ODD
HDD



Sensing Element
Monitoring Camera
Human Machine Interface
Industrial PC
Robotics



Ultrasonic
Patient Monitor
MRI
CT
Infusion Pump

PART NUMBER SELECTOR

